



ML 123

Manual-feed horizontal end-milling machine. Cutter unit pneumatic quick change. Performs milling operations, also off size between -45° and +45°. Fully protected work area. Scratchproof worktop. Forward movement on ball-bearing guides and runners ensures smooth and precise operation over the years. Self-braking motor and horizontal and vertical pneumatic clamps with low-pressure device making the machine particularly safe for the operator.

Revolver depth stop with 6 adjustable positions and micro-mist pneumatic tool lubrication (emulsified oil) speed up the work cycle. The integrated mill cutter magazine and conveyed shaving ejection make the machine tidy and clean.



TECHNICAL DATA	ML 123
Three-phase power supply	380/400 Volt - 50/60 Hz
Three-phase motor power	1.1 kW
Spindle speed	2.850 rpm
X AXIS stroke	300 mm
Clamp capacity (bxh)	200x120 mm
Max cutter diameter	160 mm
Cutter holder	Ø 27/32 mm - L 135 mm
Variable milling angle	-45°... +45°
Weight	125 kg (275 lb)

ML 124

Horizontal end-milling machine with manual or automatic feed in "A" version. The high tool rotation speed improves work quality on coated profile sections and off size. Performs milling operations, also off size between -45° and +45°. Cutter unit pneumatic quick change. Scratchproof worktop. Fully protected work area and ample internal visibility. Forward movement on ball-bearing guides and runners ensures smooth and precise operation over the years. Forward speed adjustment is hydraulic in the "A" version and the piece locking system is without approach stroke.

Horizontal and vertical pneumatic clamps with low-pressure device making the machine particularly safe for the operator. Revolver depth stop with 6 adjustable positions and micro-mist pneumatic tool lubrication (emulsified oil) speed up the work cycle. The integrated mill cutter magazine and the conveyed swarf ejection make the machine tidy and clean.



TECHNICAL DATA	ML 124
Three-phase power supply	380/400 Volt - 50/60 Hz
Three-phase motor power	1.5 kW
Spindle speed	6.000 rpm
X AXIS stroke	320 mm
Clamp capacity (bxh)	200x120 mm
Max cutter diameter	180 mm
Cutter holder	Ø 27/32mm - L 160mm
Variable milling angle	-45°... +45°
Weight	180-190 kg (396-418 lb)